

## ANTIQUE OAK

### Description

A blend of reclaimed oaks native to our region, our Antique Oak flooring is made from timbers and other interior barn wood. Planks range in color from light to medium brown and will contain evidence of their age and their former life including blackened nail holes, insect marks, weathered cracks and some patina. Antique Oak is an extremely durable hardwood floor with minimum character and minimum patina.



### Specifications

- \* FSC Recycled 100% / Contributes to LEED® MRC3: Material Reuse
- \* All planks are kiln-dried to 8%, +/-2% before being milled and graded to our consistently high standards by trimming out defects and waste.
- \* Unfinished - needs light sanding after installation before finishing with the finish of your choice
- \* Plank thickness: 3/4" (1/2" in some widths/ranges)
- \* Single width planks: 2-1/2" up to 12" (and wider depending on availability)
- \* Plank length: 18" - 12'
- \* Typically sold in ranges of four consecutive widths: 3" to 6", 4" to 7" and 5" to 8" with other ranges available. (Some of each width in the range is included in every order, e.g. 3" to 6" will contain 3", 4", 5" and 6" planks)
- \* Most economical: 2-1/2" (only)
- \* Most popular: 3" to 6" range

### Suggested Price

- \* U.S. Dollars Per square foot: From about \$8 to over \$14, not including shipping

### Prefinishing Option

- \* Available on orders of at least 500SF
- \* Contact us for pricing

### Milling Options

- \* Bevel: 1/16" and 1/8" (no charge)
- \* Bevel: Over 1/8" for a nominal charge (contact us)
- \* End-matching: nominal charge (contact us)

### Where To Use This Flooring

- \* Residences
- \* Commercial applications

### Installation Types

- \* Nail down or gluedown (with exceptions)
- \* Over radiant heat (with exceptions and precautions)
- \* On or above grade