



Antique Distressed™ Oak

(Generic: "reclaimed oak distressed face")

DOWNLOADABLE
PRODUCT
DATA SHEET

Description

Our Antique Distressed™ Oak, generically known as reclaimed oak flooring distressed face, is a blend of salvaged oak barn wood native to our region with planks ranging in color from light/medium to dark brown with "hints" of the original circular sawn timber faces. This 95% planed-smooth flooring has more evidence of age than our Antique Oak Remilled flooring and is a durable and very rustic reclaimed wood floor with maximum character and medium patina.

We are able to supply this product as engineered reclaimed hardwood flooring and/or sorted as WHITE OAK only.



Installation Methods

- * On/above grade for solid | On/above/below grade for ERA™ Engineered Flooring
- * Naildown or gluedown (w/exceptions)
- * Over in-floor radiant heat (w/exceptions and precautions)

Solid Flooring Specs

- * 100% Recycled | Contributes to LEED® MRc3: Material Reuse
- * Kiln dried to 8%, +/-2% before milling to stabilize/sanitize
- * Thickness: 3/4" (others available) | Plank Lengths: 2' - 10'
- * Widths" 3" to 10" (depending on availability) | Typ. sold in 4-width ranges of 3"-6", 4"-7", 5"-8", etc.
- * Most popular range is 3"-6", i.e. the order will contain 3", 4", 5" and 6" in varying (random) amounts
- * End-matching is standard | Beveling is optional (no charge)
- * Unfinished, prefinishing is optional. (See "Prefinishing Options" section.)

ERA™ Engineered Flooring Specs

- * Wear layers are kiln-dried to 8%, +/-2% before being bonded to a multi-layer, Baltic Birch substrate
- * CARB-II / TSCA Title VI Compliant!
- * Standard wear layer: 4 mm | Standard overall thickness: 5/8" (below 8" width) | Thicknesses of 7/16", 1/2" and 3/4" are options w/3/4" used on all widths of 8" and up
- * Widths: Typ. sold 4"-6" (no 3"), 4"-7", 5"-8", etc.
- * Standard plank length: 2' - 10'
- * End-matching is standard | Beveling is optional (no charge)
- * Can be installed on, above or below grade by nail- or glue-down method. Please discuss your installation with us beforehand.

Prefinishing Options

- * Available on most orders over 250 SF
- * Finish types: UV-catalyzed nano particle AIOx urethane or WOCA Natural (plant-based) Oil
- * Standard stains/colors are available. Custom-matching is available.
- * Contact us for pricing.

Where To Use This Flooring

- * Residences
- * Commercial applications

Aged Woods, Inc. - York, PA
(800) 233-9307 (U.S. & Canada) (717) 840-0330
<https://www.agedwoods.com>

"Eco-friendly floors since 1983"

Copyright © 1996-2024 Aged Woods, Inc. | All Rights Reserved