

Description

Our Ranch House™ Oak, generically known as skip-planed (or hit-miss) reclaimed oak, is a blend of reclaimed oak barn wood from our region with T&G planks ranging in color from smooth medium brown to dark brown. We carefully remill the timbers to retain much of the heavily textured outsides of the original circular sawn faces balanced with smooth-planed areas. This is a durable reclaimed wood remilled flooring with maximum character and maximum patina.

We are able to supply this product as engineered reclaimed hardwood flooring and/or sorted as WHITE OAK only.



Installation Methods

- * On/above grade for solid | On/above/below grade for ERA™ Engineered Flooring
- * Naildown or gluedown (w/exceptions)
- * Over in-floor radiant heat (w/exceptions and precautions)

Solid Flooring Specs

- * 100% Recycled | Contributes to LEED® MRc3: Material Reuse
- * Kiln dried to 8%, +/-2% before milling to stabilize/sanitize
- * Thickness: 3/4" (others available) | Plank Lengths: 2' - 10'
- * Widths" 3" to 10" (depending on availability) | Typ. sold in 4-width ranges of 3"-6", 4"-7", 5"-8", etc.
- * Most popular range is 3"-6", i.e. the order will contain 3", 4", 5" and 6" in varying (random) amounts
- * End-matching is standard | Beveling is optional (no charge)
- * Unfinished, prefinishing is optional. (See "Prefinishing Options" section.)

ERA™ Engineered Flooring Specs

- * Wear layers are kiln-dried to 8%, +/-2% before being bonded to a multi-layer, Baltic Birch substrate
- * CARB-II / TSCA Title VI Compliant!
- * Standard wear layer: 4 mm | Standard overall thickness: 5/8" (below 8" width) | Thicknesses of 7/16", 1/2" and 3/4" are options w/3/4" used on all widths of 8" and up
- * Widths: Typ. sold 4"-6" (no 3"), 4"-7", 5"-8", etc.
- * Standard plank length: 2' - 10'
- * End-matching is standard | Beveling is optional (no charge)
- * Can be installed on, above or below grade by nail- or glue-down method. Please discuss your installation with us beforehand.

Prefinishing Options

- * Available on most orders over 250 SF
- * Finish types: UV-catalyzed nano particle AIOx urethane or WOCA Natural (plant-based) Oil
- * Standard stains/colors are available. Custom-matching is available.
- * Contact us for pricing.

Where To Use This Flooring

- * Residences
- * Commercial applications